



LED Flood Light TL-LH3653 >>>




Features



- * Unique appearance design, simple and natural shape.
- * High-conductivity aluminum radiator, ventilation and convection design, smaller fixture and the larger power.
- * Equipped with imported light source, high luminous flux output, good light color consistency, temperature resistance, high transparency; flame retardant optical lens can be equipped with built-in honeycomb anti-glare grille.
- * Glue-free waterproof design, protection level IP65.
- * Single color/RGB/RGBW four-in-one. It supports DMX512 control system. Simple wiring makes the installation and maintenance of lights more convenient and faster.
- * Good electromagnetic compatibility, no electromagnetic interference to the surrounding environment.

Product Specification		
Model	TL-LH3653	TL-LH3654
Input voltage/power	DC24V/18W	DC24V/24W
Number of LEDs/light sources	San'an 3535/6PCS	San'an 3535/12PCS
Beam angle	15°	
Color temperature	RGB	
Installation method	Fixed	
IP rating	IP65	
Product size (L×W×H)	D110×119×153mm	D130×136×168mm
Packing size (L×W×H)	415×340×285mm	430×325×410mm
Gross weight	16.4KG (12PCS/box)	20KG (12PCS/box)
Net weight	1.2KG	1.5KG

LED Underwater Light TL-LH6201 >>>



Features



- * The shell is made of 304 stainless steel, which has excellent anti-rust capability;
- * Highly sealed and waterproof structure, and waterproof grade of IP68;
- * DC12V power supply, the safe extra-low voltage, protects personal safety;
- * Optional colors: cold, warm, neutral white, red, green, yellow, blue, mixed color.

Product Specification			
Model	TL-LH6201	TL-LH6202	TL-LH6203
Input voltage/power	DC12V/50Hz/6W	DC12V/50Hz/9W	DC12V/50Hz/12W
Number of LED lamp bead/light source	Epistar/6PCS	Epistar/9PCS	Epistar/12PCS
Beam angle	15° (30, 45, 60° optional)		
Color temperature	3000K (1900, 2100, 4000, 5700K optional)		
Control method	/		
Installation method	Fixed		
IP level	IP68		
Fixture size (Diameter×H)	Φ120×H160mm	Φ145×H180mm	Φ160×H220mm
Certificate	CE/ROHS		

LIGHT THE WORLD
ILLUMINATE THE FUTURE

LED LIGHTING

Technology Creates A Better Life



Product Description

- LED Linear Light
- LED Wall Washer
- LED Point Light Source
- LED Flood Light
- LED Underwater Light



Free match
Free to add accessories




Independent research and development
Independent mold development and production



Safe and secure
Built-in constant current drive



Structural waterproof
Integrated structural design



Professional technology
Imported high-efficiency chip



Special protection
Outdoor lightning protection and anti-static



Guangdong BaoLun Electronics Co., Ltd (Leading Audiovisual and Lighting System Manufacturer)
Factory Add: No. 56 Nanli East Road Shiqi Town, Panyu District, Guangzhou
Headquarter Add: Building No.A13-1 Yiku Industrial Park, The Hills, Dongyi Road, Panyu District, Guangzhou China
Website: www.itclighting.com info@itc-pa.com.cn

Related Products <<<



TL-LH4101
LED POINT LIGHT SOURCE



TL-LH2301
LED LINEAR LIGHT



TL-LH2406



TL-LH5407
WALKWAY LIGHT



TL-LH1010
LED WALL WASHER



TL-LH1806



TL-LH6201
LED UNDERWATER LIGHT



TL-LH6115
LED UNDERGROUND LIGHT



TL-LH6101



TL-LH5101
LED CORRUGATED LIGHT



TL-LH3101
LED FLOOD LIGHT



TL-LH3653



TL-LH7301



TL-LH7206
LED GARDEN LIGHT



TL-LH7205

LED Linear Light TL-LH2401 >>>



Features



- * Unique structure, simple and beautiful appearance, waterproof design with full sealant potting, and protection level of IP65;
- * 6063 aluminum alloy fixture, SUS304 stainless steel screw, multiple installation methods, surface electrostatic spraying paint, strong corrosion resistance, making it suitable for harsh outdoor environments;
- * It has the excellent optical performance, and the external anti-UV PC cover can effectively improve the uniformity of light mixing effects;
- * The integration of monochromatic/RGB/RGBW supports DMX512 control system; concise wiring makes the fixture installation and maintenance more convenient;

Product Specification			
Model	TL-LH2401	TL-LH2402	TL-LH2403
Input voltage/power	DC24V/12W	DC24V/6W	DC24V/50Hz/3W
Number of LED lamp bead/light source	OSRAM 2835/48PCS	OSRAM 2835/24PCS	OSRAM 2835/12PCS
Beam angle	120°		
Color temperature	3000K (1900, 2100, 4000, 5700K optional)		
Control method	/		
Installation method	Fixed (fastener is optional)		
IP level	IP65		
Fixture size (L×W×H)	1000×28×40mm	500×28×40mm	300×28×40mm
Net weight	0.9KG	0.5KG	0.3KG
Certificate	CE/ROHS		

LED Wall Washer TL-LH1010 >>>



Features



- * Simple appearance design, economical and practical structure;
- * The fixture has high luminous uniformity and brightness;
- * Electronic constant current program design ensures stable quality and long;
- * The light projection angle and position are adjustable, making it always in the best state for the most satisfactory lighting effects.

Product Specification			
Model	TL-LH1010	TL-LH1011	TL-LH1012
Input voltage/power	DC24V/24W	DC24V/12W	DC24V/6W
Number of LED bead/light source	SMD3030/24PCS	SMD3030/12PCS	SMD3030/12PCS
Beam angle	30° (45°, 60°, 20°45° optional)		
Color temperature	3000K (1900K, 2100K, 2700K, 4000K, 5700K optional)		
Installation method	Fixed		
IP rating	IP65		
Product size (L×W×H)	1000×34×69mm	500×34×69mm	300×34×69mm
Packaging size (L×W×H)	1070×340×230mm	570×340×355mm	370×340×355mm
Gross weight	15.5KG (15PCS/box)	14.5KG (25PCS/box)	9.5KG (25PCS/box)
Net weight	0.9KG	0.5KG	0.3KG

LED Point Light Source TL-LH6203 >>>



Features



- * Original appearance design, simple overall appearance, angular, exquisite and beautiful, structural waterproof design, waterproof grade IP65;
- * High grayscale, high refresh, flicker-free and color design;
- * Uniform and soft luminescence, no dark areas.

Product Specification			
Model	TL-LH4101	TL-LH4102	TL-LH4103
Input voltage/power	DC24V/50Hz/3W	DC24V/50Hz/5W	DC24V/50Hz/3W
Number of LEDs/light sources	EPISTAR 3535/12PCS	EPISTAR 3535/24PCS	EPISTAR 3535/12PCS
Beam angle	120°		
Color temperature	3000K (1900, 2100, 4000, 5700K optional)		
Installation method	Fixed		
IP rating	IP65		
Size (L×W×H)	122×94×54mm		
Packing size (L×W×H)	535×405×255		
Gross weight	16KG (48PCS/box)		
Net weight	0.3KG		
Certification	CE/ROHS		